



[Home](#) / [Standard products](#) / [Rubber hoses](#) / [Cooling water hose DIN 73411-79](#)

---



- mandrel wound
- Inner tube: EPDM, black, smooth
- Cover: EPDM, black, fabric pattern
- Reinforcement: Textile cord inlay
- Temperature: -40 °C to +120°C

| Art. No.  | Inner Ø x Wall<br>[mm] | Operating pressure<br>[bar] | Weight<br>[g/m] | Roll length<br>[m] |
|-----------|------------------------|-----------------------------|-----------------|--------------------|
| 0800016   | 8 x 3,5                | 6                           | 150             | 40                 |
| 0800020   | 20 x 3,5               | 6                           | 300             | 40                 |
| 0800128   | 22 x 3,5               | 6                           | 320             | 40                 |
| 0800123   | 25 x 3,5               | 6                           | 360             | 40                 |
| 0800008   | 28 x 4,0               | 6                           | 420             | 40                 |
| 0800230   | 30 x 4,0               | 6                           | 460             | 40                 |
| 0800231   | 32 x 4,0               | 6                           | 490             | 40                 |
| 0800021   | 35 x 4,0               | 6                           | 540             | 40                 |
| 0800077   | 38 x 5,0               | 6                           | 780             | 40                 |
| 0800041   | 40 x 5,0               | 6                           | 820             | 40                 |
| 0800109-1 | 42 x 5,0               | 850                         | 40              |                    |
| 0800081   | 45 x 5,0               | 6                           | 900             | 40                 |
| 0800093   | 48 x 5,0               | 6                           | 960             | 40                 |
| 0800051   | 50 x 5,0               | 6                           | 1.000           | 40                 |
| 0800232   | 55 x 5,0               | 6                           | 1.100           | 40                 |

| Art. No. | Inner Ø x Wall<br>[mm] | Operating pressure<br>[bar] | Weight<br>[g/m] | Roll length<br>[m] |
|----------|------------------------|-----------------------------|-----------------|--------------------|
| 0800092  | 60 x 5,0               | 6                           | 1.200           | 40                 |
| 0800234  | 63,5 x 5,0             | 5                           | 1.250           | 40                 |
| 0800074  | 65 x 5,0               | 5                           | 1.260           | 40                 |
| 0800233  | 70 x 5,0               | 5                           | 1.350           | 40                 |
| 0800075  | 75 x 5,0               | 5                           | 1.460           | 40                 |
| 0800235  | 80 x 6,0               | 4                           | 1730            | 20                 |
| 0800236  | 85 x 6,0               | 4                           | 1.750           | 20                 |
| 0800237  | 90 x 6,0               | 4                           | 2.200           | 20                 |
| 0800078  | 100 x 6,25             | 3                           | 2.400           | 20                 |
| 0800239  | 110 x 6,0              | 3                           | 2.560           | 20                 |
| 0800238  | 114 x 6,0              | 3                           | 2.580           | 20                 |
| 0800240  | 120 x 6,5              | 3                           | 3.150           | 20                 |
| 0800241  | 125 x 6,5              | 3                           | 3.200           | 20                 |
| 0800242  | 140 x 6,5              | 3                           | 3.540           | 20                 |
| 0800243  | 152 x 7,0              | 3                           | 3.800           | 20                 |

| Art. No. | Inner Ø x Wall<br>[mm] | Operating pressure<br>[bar] | Weight<br>[g/m] | Roll length<br>[m] |
|----------|------------------------|-----------------------------|-----------------|--------------------|
| 0800110  | 160 x 7,0              | 3                           | 4.100           | 20                 |
| 0800244  | 200 x 7,5              | 3                           | 5.050           | 20                 |

#### DIN 73411-79, extruded

- Core: EPDM, black, smooth
- Cover: EPDM, black, smooth
- Reinforcement: Polyester inlay
- Operational pressure: 3 bar
- Burst pressure: 9 bar
- Temperature: -40 °C to +120 °C

| Art. No. | Inner Ø x Wall<br>[mm] | Weight<br>[g/m] | Roll length<br>[m] |
|----------|------------------------|-----------------|--------------------|
|          | 10 x 3,5               | 150             | 100                |
|          | 12 x 3,5               | 160             | 100                |
| 0800085  | 13 x 3,5               | 170             | 60                 |
|          | 15 x 3,5               | 190             | 60                 |
|          | 16 x 3,5               | 200             | 60                 |

| Art. No. | Inner Ø x Wall<br>[mm] | Weight<br>[g/m] | Roll length<br>[m] |
|----------|------------------------|-----------------|--------------------|
|          | 18 x 3,5               | 230             | 60                 |
| 0800027  | 19 x 3,5               | 240             | 60                 |

Silicone cooling water hoses, bends and sleeves available upon request!

© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

[+49 \(0\) 5121 / 28995-0](tel:+495121289950)

[E-Mail](#)

## Cookie-Settings

- ☒ Technically essential
- ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential